

Crown

Tuft gauge	1/10 cut pile	ISO 2424
Pilecomposition	100% PA SDN	ISO 2424
Primary Backing	Woven	ISO 2424
Secondary backing	AB	ISO 2424
Width	400 cm ± 1%	EN 986
Pile Density	0.150 gr/cm ³	ISO 8543
Pile Weight	950 gr/m ²	ISO 8543
Total weight	AB : 1800 gr/m ² ± 15%	ISO 8543
Pile height	8.5 mm	ISO 1765
Total Height	AB : 10.5 mm	ISO 1765
Number of knots	158.000/m ² -7.5% .+10%	ISO 1763
Fire Classification	Cfl-S1	EN 13501-1
Transversal resistance	10 ¹¹ Ω	ISO 10965
Thermal resistance	0.093 M ² KW	ISO 8302
Light fastness	≥ 5	105-B02
Wearebility	≥ 4	105-X12
Water fastness	≥ 4	105-E01
Electrostatic charging	<2 kV	ISO 6356
Luxury class	LC3	EN 1307
Pictures	www.condorcontract.com	

Floorsymbols



Certificates



2019

Condor Carpets
Euroweg 3
8061 SB Hasselt

EN1307

DOP: C-003AC391

Reaction to fire:
Cfl-s1
1668

Slip resistance: DS

Resilient floor
covering to be
used within a
building



www.blauer-engel.de/uz128

